



# Suite

COLLECTION

18 STYLES IN 13 COLORWAYS

**T**TOTALLY  
ENTERPRISES, LLC







# Stritex

**XP** 1004-C9795 Boardroom

Style Number ..... 1004  
Pattern Repeat ..... 3.5" W x None  
Tufted Yarn Weight ..... 29 oz  
Gauge ..... 1/10  
Construction ..... Tip Sheared Enhanced Loop  
Face Yarn ..... 100% Solution Dyed Nylon  
Yarn Spec ..... Twisted & heatset for high performance  
Pile Height ..... 0.149  
Primary Backing ..... 4 oz Woven Polypropylene  
Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
Tile Backing ..... Vinyl composite with recycled content  
Width Broadloom ..... 12'  
Tile Size ..... 24" x 24"



Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
Broadloom Adhesive ..... Totally Premium Broadloom Adhesive  
Tile Adhesive ..... Totally Premium Tile Adhesive  
Flammability ..... Passes Class 1 (ASTM E-648)  
Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
Dye Lot Size ..... Unlimited  
Custom Colors & Weight ..... Please Inquire  
Origin ..... Made in USA  
LEED ..... Contributes to Leed Credits  
CRI ..... Green Label Plus  
Warranty ..... Tile: limited lifetime warranty    Broadloom: 10-year limited warranty





# Grid

**XP** 1019-C9795 Boardroom

Style Number .....	1019
Pattern Repeat .....	.6"W x 6.6"L
Tufted Yarn Weight .....	46 oz.
Gauge .....	1/10
Construction .....	Shear
Face Yarn .....	100% Solution Dyed Nylon
Yarn Spec .....	Cortex™ Twisted & Heatset for High Performance.
Tufts per Sq. Inch .....	200 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height .....	0.156
Primary Backing .....	4 oz Woven Polypropylene
Secondary Backing .....	High Performance Backing System with 18x5 Lino ActionBac
Treatments .....	Commercial carpet soil protection & static control
Width Broadloom .....	12'



Post Installation Protection .....	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Broadloom Adhesive .....	Totally Premium Broadloom Adhesive
Flammability.....	Passes Class 1 (ASTM E-648)
Electrostatic Propensity .....	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size .....	Unlimited
Custom Colors & Weight .....	Please Inquire
Origin.....	Made in USA
LEED .....	Contributes to Leed Credits
CRI .....	Green Label Plus
Warranty .....	Broadloom: 10 year limited warranty





# Executive

**XP** 1020-C9795 Boardroom

Style Number .....	1020
Pattern Repeat .....	None
Tufted Yarn Weight .....	66 oz.
Gauge .....	1/10
Construction .....	Shear
Face Yarn .....	100% Solution Dyed Nylon
Yarn Spec .....	Cortex™ Twisted & Heatset for High Performance.
Tufts per Sq. Inch .....	200 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height .....	0.281
Primary Backing .....	4 oz Woven Polypropylene
Secondary Backing .....	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing .....	Vinyl composite with recycled content
Width Broadloom.....	12'



Tile Size .....	24" x 24"
Treatments .....	Commercial carpet soil & static control
Post Installation Protection .....	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Broadloom Adhesive.....	Totally Premium Broadloom Adhesive
Tile Adhesive.....	Totally Premium Tile Adhesive
Flammability.....	Passes Class 1 (ASTM E-648)
Electrostatic Propensity .....	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size .....	Unlimited
Custom Color & Weight .....	Please Inquire
Origin.....	Made in USA
LEED .....	Contributes to Leed Credits
CRI .....	Green Label Plus
Warranty .....	Tile: limited lifetime warranty    Broadloom: 10-year limited warranty





# Brilliance

**XP** 1008-C9795 Boardroom

Style Number ..... 1008  
 Pattern Repeat ..... None  
 Tufted Yarn Weight ..... 52 oz  
 Gauge ..... 1/10  
 Construction ..... Tip Sheared Enhanced Loop  
 Face Yarn ..... 100 % Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 200 [gauge x stitch rate x tufts per stitch]  
 Pile Height ..... 0.187  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Tile Backing ..... Vinyl composite with recycled content  
 Width Broadloom ..... 12'



Tile Size ..... 24" x 24"  
 Treatments ..... Commercial carpet soil protection & static control  
 Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive ..... Totally Premium Broadloom Adhesive  
 Tile Adhesive ..... Totally Premium Tile Adhesive  
 Flammability ..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Colors & Weight ..... Please Inquire  
 Origin ..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Tile: limited lifetime warranty. Broadloom: 10 year limited warranty





# Knit

**XP** 1015-C9795 Boardroom

Style Number ..... 1015  
 Pattern Repeat ..... 4"W x .57"L  
 Tufted Yarn Weight ..... 32 oz.  
 Gauge ..... 1/10  
 Construction ..... Loop  
 Face Yarn ..... 100% Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 140 (Gauge x Stitch Rate x Tufts/Stitch)  
 Pile Height ..... 0.125  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Treatments ..... Commercial carpet soil protection & static control  
 Width Broadloom ..... 12'



Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive ..... Totally Premium Broadloom Adhesive  
 Flammability..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Colors & Weight ..... Please Inquire  
 Origin..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Broadloom: 10 year limited warranty





# Connect

Style Number ..... 1017  
 Pattern Repeat ..... 6"W x 3.2"L  
 Tufted Yarn Weight ..... 30 oz.  
 Gauge ..... 1/10  
 Construction ..... Loop  
 Face Yarn ..... 100 % Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 150 (Gauge x Stitch Rate x Tufts/Stitch)  
 Pile Height ..... 0.125  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Treatments ..... Commercial carpet soil protection & static control  
 Width Broadloom ..... 12'



**XP** 1017-C9795 Boardroom

Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive ..... Totally Premium Broadloom Adhesive  
 Flammability..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Colors & Weight ..... Please Inquire  
 Origin..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Broadloom: 10 year limited warranty





# Bead

Style Number ..... 1016  
 Pattern Repeat ..... .8"W x .72"L  
 Tufted Yarn Weight ..... 56 oz.  
 Gauge ..... 1/10  
 Construction ..... Shear  
 Face Yarn ..... 100 % Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 200 (Gauge x Stitch Rate x Tufts/Stitch)  
 Pile Height ..... 0.156  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Width Broadloom..... 12'  
 Treatments ..... Commercial carpet soil & static control



**XP** 1018-C9795 Boardroom

Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive..... Totally Premium Broadloom Adhesive  
 Flammability..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Color & Weight ..... Please Inquire  
 Origin..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Broadloom: 10 year limited warranty





# Chain

**XP** 1018-C9795 Boardroom

Style Number ..... 1018

Pattern Repeat ..... .6"W x .75"L

Tufted Yarn Weight ..... 34 oz.

Gauge ..... 1/10

Construction ..... **CHAIN** Loop

Face Yarn ..... 100% Solution Dyed Nylon

Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.

Tufts per Sq. Inch ..... 210 (Gauge x Stitch Rate x Tufts/Stitch)

Pile Height ..... 0.125

Primary Backing ..... 4 oz Woven Polypropylene

Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac

Treatments ..... Commercial carpet soil protection & static control

Width Broadloom ..... 12'



Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.

Broadloom Adhesive ..... Totally Premium Broadloom Adhesive

Flammability..... Passes Class 1 (ASTM E-648)

Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less

Dye Lot Size ..... Unlimited

Custom Colors & Weight ..... Please Inquire

Origin..... Made in USA

LEED ..... Contributes to Leed Credits

CRI ..... Green Label Plus

Warranty ..... Broadloom: 10 year limited warranty



# Multi-Strident Loop

**XP** 1012-C9795 Boardroom

Style Number .....	1012
Pattern Repeat .....	9.6W" X 38.5" L
Tufted Yarn Weight .....	46 oz
Gauge .....	1/10
Construction .....	Loop
Face Yarn .....	100% Solution Dyed Nylon
Yarn Spec .....	Cortex™ Twisted & Heatset for High Performance.
Tufts/sq in. ....	220 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height .....	0.218
Primary Backing .....	4 oz Woven Polypropylene
Secondary Backing .....	High Performance Backing System with 18x5 Lino ActionBac
Width Broadloom .....	12'
Treatments .....	Commercial carpet soil protection & static control



Post Installation Protection .....	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Broadloom Adhesive.....	Totally Premium Broadloom Adhesive
Flammability.....	Passes Class 1 (ASTM E-648)
Electrostatic Propensity .....	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size .....	Unlimited
Custom Colors & Weight .....	Please Inquire
Origin.....	Made in USA
LEED .....	Contributes to Leed Credits
CRI .....	Green Label Plus
Warranty .....	Broadloom: 10 year limited warranty





# Multi-Strident

**XP** 1013-C9795 Boardroom

Style Number ..... 1013  
 Pattern Repeat ..... 9.6" W x 38.5" L  
 Tufted Yarn Weight ..... 46 oz.  
 Gauge ..... 1/10  
 Construction ..... Tip Sheared Enhanced Loop  
 Face Yarn ..... 100% Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 220 (Gauge x Stitch Rate x Tufts/Stitch)  
 Pile Height ..... 0.187  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Tile Backing ..... Vinyl composite with recycled content  
 Width Broadloom..... 12'



Tile Size ..... 24" x 24"  
 Treatments ..... Commercial carpet soil & static control  
 Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive..... Totally Premium Broadloom Adhesive  
 Tile Adhesive..... Totally Premium Tile Adhesive  
 Flammability..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Color & Weight ..... Please Inquire  
 Origin ..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Tile: Limited lifetime warranty Broadloom: 10 year limited warranty





# Tailor Made

**XP** 1014-C9795 Boardroom

Style Number ..... 1014  
Pattern Repeat ..... 4"W x None  
Tufted Yarn Weight ..... 45 oz.  
Gauge ..... 1/10  
Construction ..... Loop  
Face Yarn ..... 100% Solution Dyed Nylon  
Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
Tufts per Sq. Inch ..... 165 (Gauge x Stitch Rate x Tufts/Stitch)  
Pile Height ..... 0.156  
Primary Backing ..... 4 oz Woven Polypropylene  
Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
Treatments ..... Commercial carpet soil protection & static control  
Width Broadloom ..... 12'



Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
Broadloom Adhesive ..... Totally Premium Broadloom Adhesive  
Flammability..... Passes Class 1 (ASTM E-648)  
Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
Dye Lot Size ..... Unlimited  
Custom Colors & Weight ..... Please Inquire  
Origin..... Made in USA  
LEED ..... Contributes to Leed Credits  
CRI ..... Green Label Plus  
Warranty ..... Broadloom: 10 year limited warranty



# Matte Herringbone

**XP** 1025-C9795 Boardroom

Style Number ..... 1025  
 Pattern Repeat ..... .6"W x 0.1"L  
 Tufted Yarn Weight ..... 52 oz.  
 Gauge ..... 1/10  
 Construction ..... Shear  
 Face Yarn ..... 100% Solution Dyed Nylon  
 Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
 Tufts per Sq. Inch ..... 240 (Gauge x Stitch Rate x Tufts/Stitch)  
 Pile Height ..... 0.218  
 Primary Backing ..... 4 oz Woven Polypropylene  
 Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
 Tile Backing ..... Vinyl composite with recycled content  
 Width Broadloom..... 12'



Tile Size ..... 24" x 24"  
 Treatments ..... Commercial carpet soil & static control  
 Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
 Broadloom Adhesive..... Totally Premium Broadloom Adhesive  
 Tile Adhesive..... Totally Premium Tile Adhesive  
 Flammability..... Passes Class 1 (ASTM E-648)  
 Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
 Dye Lot Size ..... Unlimited  
 Custom Color & Weight ..... Please Inquire  
 Origin ..... Made in USA  
 LEED ..... Contributes to Leed Credits  
 CRI ..... Green Label Plus  
 Warranty ..... Tile: Limited lifetime warranty Broadloom: 10 year limited warranty



# Fine Herringbone

**XP** 1026-C9795 Boardroom

Style Number ..... 1026  
Pattern Repeat ..... 4"W x .67"L  
Tufted Yarn Weight ..... 53 oz.  
Gauge ..... 1/10  
Construction ..... Shear  
Face Yarn ..... 100% Solution Dyed Nylon  
Yarn Spec ..... Cortex™ Twisted & Heatset for High Performance.  
Tufts per Sq. Inch ..... 240 (Gauge x Stitch Rate x Tufts/Stitch)  
Pile Height ..... 0.187  
Primary Backing ..... 4 oz Woven Polypropylene  
Secondary Backing ..... High Performance Backing System with 18x5 Lino ActionBac  
Tile Backing ..... Vinyl composite with recycled content  
Width Broadloom..... 12'



Tile Size ..... 24" x 24"  
Treatments ..... Commercial carpet soil & static control  
Post Installation Protection ..... Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.  
Broadloom Adhesive..... Totally Premium Broadloom Adhesive  
Tile Adhesive..... Totally Premium Tile Adhesive  
Flammability..... Passes Class 1 (ASTM E-648)  
Electrostatic Propensity ..... Passes AATCC - 134 @ 3.5 KV or less  
Dye Lot Size ..... Unlimited  
Custom Color & Weight ..... Please Inquire  
Origin..... Made in USA  
LEED ..... Contributes to Leed Credits  
CRI ..... Green Label Plus  
Warranty ..... Tile: Limited lifetime warranty Broadloom: 10 year limited warranty