

Totally Carpet Specs

Style Name	Herringbone
Style Number	1010
Pattern Repeat	6.4" W x 1" H
Tufted Yarn Weight	52 oz
Gauge	1/10
Construction	Tip Sheared Enhanced Loop
Face Yarn	100 % Solution Dyed Nylon
Yarn Spec	"Cortex" (Patent Pending) Twisted & Heatset for High Performance.
Tufts per Sq. Inch	240 [gauge x stitch rate x tufts per stitch]
Pile Height	0.218
Primary Backing	4 oz Woven Polypropylene
Secondary Backing	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing	Vinyl composite with recycled content
Width Broadloom	12'
Tile Size	24" x 24"
Treatments	Commercial carpet soil protection & static control
Post Installation Protection	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Recommended Adhesive Broadloom	Totally Premium Broadloom Adhesive
Recommended Adhesive Tile	Totally Premium Tile Adhesive
Flammability	Passes Class 1 (ASTM E-648)
Electrostatic Propensity	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size	Unlimited
Custom Colors & Weight	Please Inquire
Origin	Made in USA
LEED	Contributes to Leed Credits
CRI	Green Label Plus
Warranty	Tile: limited lifetime warranty. Broadloom: 10 year limited warranty

