



Totally Carpet Specs

Style Name	Source
Style Number	1038
Pattern Repeat	1" W x 1" L
Tufted Yarn Weight	31 oz.
Gauge	1/10
Construction	Tip Shear
Face Yarn	100 % Solution Dyed Nylon
Yarn Spec	Twisted & Heatset For High Performance
Tufts Per Sq Inch	160 (Gauge x Stitch / Inch x Tufts/Stitch
Pile Height	0.156
Primary Backing	4 oz Woven Polypropylene
Secondary Backing	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing	Vinyl composite with recycled content
Width Broadloom	12"
Tile Size	24" x 24"
Treatments	Commercial carpet soil & static control
Post Installation Protection	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Recommended Adhesive Broadloom	Totally Premium Broadloom Adhesive
Recommended Adhesive Tile	Totally Premium Tile Adhesive
Flammability	Passes Class 1 (ASTM E-648)
Electrostatic Propensity	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size	Unlimited
Custom Color & Weight	Please Inquire
Origin	Made in USA
LEED	Contributes to Leed Credits
CRI	Green Label Plus
Warranty	Tile: Limited lifetime warranty Broadloom: 10 yr limited warranty